De Dietrich

Induction hob Ref.: DPI4301BP







Product highlights

TENOR ZONE 5500W The most powerful and fastest double ring inductor on the market! Sear your meat to release their full flavors and bring to the boil at unprecedented speed (time saving of 25% vs. 4600W), with identical energy consumption.

Boil Function that can boil from 0.5 L up without any overflow and without taking care of timeor power settings. You just need to set water quantity and validate.

Smart Functions Your table is equiped with clever functions such as ICS to immediately identify the most suitable hob and Elapsed time, which displays on the keyboard the time that has elapsed since the last adjustment of the power of a zone.

GENERAL		
Brand	DE DIETRICH	
Commercial code	DPI4301BP	
EAN code	3660767991514	
Customs code	85166050	

FEATURES	
Construction type	Built-in
Hob type	Induction
Top material	Glass ceramic
Width (cm)	65
Energy type	Electric
Colour	Black
Finishing	R2 rounded edges
Number of zones	3
Control type	Touch-sensitive buttons
Electronic type	Red Led
Type ot timer	Electronic 99 min

CONNECTIVITY	
Connectivity	No
Connectivity type	
Features	
Culinary guide functions	

De Dietrich

Induction hob Ref.: DPI4301BP

PERFORMANCE						
	Cooking zone A	Cooking zone B	Cooking zone C	Cooking zone D	Cooking zone E	Cooking zone F
Number of cooking zone	1	1	1			
Type of heating element	Induction (Circular)	Induction (Circular)	Induction (Double ring)			
Position of heating element	Front left	Rear left	Centre right			
Dimensions of the heating element (mm	160	230	300			
Max. power of the heating element in W	2400	3700	5500			
Number of position(s) / cooking zone	20	20	20			
Timer	Yes	Yes	Yes			
Direct access	Warm keeping;Simmer;Sear;Boost	Warm keeping;Simmer;Sear;Boost	Warm keeping;Simmer;Sear;Boost			
Electrical energy consumption per zone (EC) Wh/kg	175,1	170,2	168,9			

FLEXIBLES ZONES	
Flexible zone	No
Flexible zone 1	
Flexible zone 2	
Flexible zone 3	
Flexible zone 4	

FUNCTIONS AND ACCESSORIES	
Functions	Boil;Boost;Clean lock;Automatic pan recognition;Elapsed time;ICS;Recall;Switch;Lock
Automatic recipes	
Step-by-step recipes	
Probe (with holder)	No
Probe functions	
Accessories supplied	Seal
Optional accessories	

SAFETY	
Safety devices	Pack 10 securities
Power indicator	Flashing 0 in display

INSTALLATION	
Hob maximum electric power input (kW)	7.4
Fuse (A)	32
Voltage (V)	220-240
Frequency (Hz)	50/60
Three-phase connection	
Total electrical energy consumption (EC)	171,4
Standby consumption (W)	< 0.5
Dimensions of the unboxed product HxWxD (mm)	59X650X515
Dimensions of the packed product HxWxD (mm)	140X750X600
Worktop cut-out dimensions WxD (mm)	560X490
Length of power supply cord (cm)	130
Plug type	Without
Net weight (kg)	11
Gross weight (kg)	11.5

MANUFACTURING		
Country of origin	France	
Availability of spare parts (years)	20	
Repair Index		